

Canon**XF705**

ÇÖZÜNÜRLÜK	RENK ÖRNEKLEME	BİT DERİNLİĞİ	KARE HIZI	KODEK	Mbps
3840 x 2160	YCC 4:2:2	10 bit	59,94P, 29,97P, 23,98P, 50.00P, 25.00P	H.265/HEVC	160Mbps/110Mbps
1920 x 1080	YCC 4:2:2	10 bit	59,94P, 29,97P, 23,98P, 50.00P, 25.00P	H.265/HEVC	60Mbps/45Mbps
			59.94i, 50.00i		60Mbps/45Mbps
			120P, 100P		180 Mbps
3840 x 2160	YCC 4:2:0	8 bit	29,97P, 23,98P,25,00P	H.264/XF-AVC	160 Mbps
1920 x 1080	YCC 4:2:0	8 bit	59,94P, 29,97P, 23,98P, 50.00P, 25.00P	H.264/XF-AVC	45 Mbps
			59.94i, 50.00i	H.264/XF-AVC	35 Mbps
			120P, 100P	H.264/XF-AVC	45 Mbps
1280 x 720	YCC 4:2:0	8 bit	59,94P	H.264/XF-AVC	180 Mbps
1920 x 1080	YCC 4:2:0	8 bit	59,94P, 29,97P, 23,98P, 50.00P, 25.00P	H.264/MP4	8 Mbps
					35Mbps/8Mbps